

## Steinberg UR Series Comparison Chart

General Features	UR22	UR44	UR28M	UR824
Connection type	USB 2.0	USB 2.0	USB 2.0	USB 2.0
Design	Desktop (1/3 19", 1HU)	Desktop (2/3 19", 1HU)	Desktop	19" rack unit, 1 HU
USB-powered	Yes	No	No	No
AD/DA	24-Bit	24-Bit	24-Bit	24-Bit
Maximum sample rate	192 kHz	192 kHz	96 kHz	192 kHz
Class compliant mode	No	Yes	Yes	Yes
Loopback function	No	Yes	Yes	Yes

Connectivity	UR22	UR44	UR28M	UR824
Total number of I/O	2/2	6/4	6/8	24/24
Analog inputs	2 Combo	4 Combo, 2 TRS	2 Combo, 2 TRS	8 Combo
Microphone inputs	2 (D-PRE)	4 (D-PRE)	2 (D-PRE)	8 (D-PRE)
Inputs with HI-Z	1	2	2	2
Analog outputs	2	4	6	8
Phantom power	2	4	2	8
Headphones output	1	2	2	2
Digital In ADAT	No	No	No	2
Digital Out ADAT	No	No	No	2
Digital In S/PDIF	No	No	1	2 (via ADAT optical)
Digital Out S/PDIF	No	No	1	2 (via ADAT optical)
WordClock I/O	No	No	No	Yes

<b>MIDI I/O</b>	Yes	Yes	No	No
<b>Pad switch per channel</b>	No	No	2	8
<b>Hardware based zero-latency-monitoring</b>	Yes	No	No	No

<b>DSP Features</b>	<b>UR22</b>	<b>UR44</b>	<b>UR28M</b>	<b>UR824</b>
<b>Latency-free monitoring with FX (dspMixFx)</b>	No	Yes	Yes	Yes
<b>True Integrated Monitoring with FX in Cubase</b>	No	Yes	Yes	Yes
<b>Guitar Amp Classics</b>	No	Yes*	Yes	Yes
<b>REV-X Reverb</b>	No	Yes	Yes	Yes
<b>Sweet Spot Morphing Channel Strip</b>	No	4	4	8
<b>Phase switch per channel</b>	No	Yes, with computer (1-4)	Yes, with computer (1-4)	Yes, with computer (1-8)
<b>High-Pass filter</b>	No	Yes, with computer (1-4)	Yes, with computer (1-4)	Yes, with computer (1-8)

\* DSP-support for Guitar Amp Classics will be available with the upcoming version 2 update for UR44.

<b>General Specifications</b>	<b>UR22</b>	<b>UR44</b>	<b>UR28M</b>	<b>UR824</b>
<b>Color</b>	Silver and black	Silver and black	Silver and black	Silver and black
<b>Weight</b>	998 g	1.6 kg	1.6 kg	3.1 kg
<b>Dimensions (W x H x D in mm)</b>	158.6 x 45.4 x 158.3	252 x 47 x 158	291 x 59 x 164	480 x 44 x 275
<b>Bundled software</b>	Cubase AI	Cubase AI Basic FX Suite	Cubase AI Basic FX Suite	Cubase AI Basic FX Suite

**Unique Features**

**UR22**

**UR44**

**UR28M**

**UR824**

Full-metal casing

Full-metal casing

Monitor control with DIM, Mono and Mute fed by 3x3 matrix,

JET PLL ultra-low jitter support

Ultra-mobile

2-Track in for reference source